Rolling Towers

Layher Uni Standard Tower Instructions for Assembly and Use

Mobile working platforms to DIN EN 1004: 2005-03

Working platform 0.75 x 2.85 m

max. working height: indoors 13.6 m outdoors 9.6 m

Load bearing capacity 2.0 kN/m² on max. one working level (scaffold group 3 to DIN EN 1004 : 2005-03)







More Possibilities. The Scaffolding System.



For outdoor use observe height limits.

Layher Uni Standard Tower



¹⁾ Values in brackets: minimum tower height incl. spigots.



¹⁾ Values in brackets: minimum tower height incl. spigots.

Tower models with stabilizers, extendable

Layher Uni Standard Tower

For outdoor use observe height limits.



1) Values in brackets: minimum tower height incl. spigots.



Tower models with stabilizers, 5 m

Layher Uni Standard Tower

For outdoor use observe height limits.



¹⁾ Values in brackets: minimum tower height incl. spigots.





For **outdoor use** observe height limits.

Tower Models 1201 – 1206						
Tower Model	1201	1202	1203	1204	1205	1206
Working height (m) 🔶	3.5	4.6	5.6	6.6	7.6	8.6
Scaffold height 1) (m)	2.70 (2.45)	3.85 (3.60)	4.85 (4.60)	5.85 (5.60)	6.85 (6.60)	7.85 (7.60)
Platform height (m) 🔶 🔨	1.5	2.6	3.6	4.6	5.6	6.6
Weight (kg) [without ballast]	102.0	183.2	195.8	209.0	264.8	270.8

1 Values in brackets: minimum tower height incl. spigots.



 $^{\eta}$ Values in brackets: minimum tower height incl. spigots.



Layher Uni Standard Tower

▶ Pay attention to the General Assembly and Use Instructions on page 24. The examples shown of the tower types 1108 – 1111, 1128 – 1131, 1208 – 1211 are designed for use indoors. According to the regulations in force since January 1st 1987, the permissible maximum platform height outdoors is 8 m. Pay attention to the parts list and ballasting tables on pages 11–13.



deck claws and push them outwards as far as possible in order to brace the ladder frames $\boxed{6}$.

6



▶ 3 Basic assembly

▶<u>3.1</u> Tower Model 1201



1. The castors 🗇 of the tower type 1201 are inserted into the ladder frame 🕒 and secured against falling out by fastening the wing screws on the spindle nuts.

2. Connect both ladder frames with 2 Uni-girders 9. Clip the access deck run onto the 4th ladder rung from the bottom. The snap-on claws of all parts are to be locked onto the ladder rungs from above.

3. Mount the toe boards 2.85 m $\fbox{2}$ onto the ladder frames $\fbox{6}$ and secure them by fitting the end toe boards $\fbox{3}$.

Layher Uni Standard Tower

In order to remove the different parts, depress the locking clips of the snap-on claws. The red claws on the deck enable a single person to assemble or dismantle them easily; open them at one end and rest the base of the clips on the rung. Now open the opposite clips and remove the deck.

Level the tower using the threaded spindles.



1. Insert the castors into the mobile beam and secure against falling out by fastening the wing screws on the spindle nuts.

3. Mount the two ladder frames **6** and secure with spring clips **11**.

4. Mount both diagonal braces ③ to the inside of the deck claws and push them outwards as far as possible in order to brace the ladder frames ⑤.

5. For tower models 1202, 1205 and 1206 only, an access deck \fbox has to be placed on the eighth rung of the ladder frame \fbox .

6. Take care that the deck ¹¹⁴ is positioned centrally under the ladder frames ⁶. Level the tower using the threaded spindles.

For the following assembly steps, tower types 1202 and 1203 see chapter 5; for tower models 1204-1206 see chapter 4.



Tower types 1215 and 1216 with adjustable mobile beam 3 are intended for **outdoor use**.

1. Insert the castors 1 into the adjustable mobile beam 3 and secure them against falling out by fastening the wing screws on the spindle nuts.

2. Fix the base strut **5** to the deck supports of the adjustable mobile beam **3** and mount the deck **14** onto the deck supports.

3. Connect the mobile beam ③ with the base ledger ④, fitting the base ledger ④ over the protruding stub at the end of the adjustable mobile beam ③. After alignment drive in the wedge.

4. Add two ladder frames **6** and secure with spring clips **11**.

5. Mount both diagonal braces (B) inside the deck claws and push them outwards as far as possible in order to brace the ladder frames (G).

6. For tower types 1215, 1216, 1209 and 1210, install an access deck 10 on the 8th rung of the ladder frame 6.

7. On tower types 1207, 1208 and 1211 mount two guardrails 🔽 on the 8th rung. No access deck 🔟 is necessary.

8. The horizontal gap between two decks or between decks and ledgers must not exceed 25 mm.

9. Take care that the deck ^[14] is positioned centrally under the ladder frames ^[6]. Level the tower using the threaded spindles.

For the following assembly steps see chapter 4.



▶ 4 Assembling the intermediate platform



1. During assembly and dismantling, system decks or scaffold planks acc. to DIN 4420 (minimum 28 x 4.5 x 350 cm long) must be used as auxiliary decks at maximum height intervals of 2.0 m. These auxiliary decks, providing a safe footing for assembly and dismantling, are removed after the erection. Each platform must be completely boarded.

2. Continue assembly by adding ladder frames bracing them with guardrails in accordance with the examples. Secure the joints of the ladder frames with spring clips 11.

3. Access decks [™] are to be built in at maximum height intervals of 4 m. If these access decks serve as intermediate platforms for ascending, two guardrails [™] at each side are required only.

Layher Uni Standard Tower

When they are used as a working platform, double guardrails and toe boards (see chapter 4) are to be built in. In this case the top or any other working level must not be used. The toe boards there should be removed.

After assembly the guardrails $\boxed{2}$ and diagonal braces $\boxed{8}$ should be pushed outwards as far as possible.

4. When assembling the towers, care is needed to ensure the correct order of the diagonal braces (a), the guardrails (2) and the access decks (10) (see the Tower Types drawing page 2). Do not add upper ladder frames (6) until the ladder frames (6) below are braced properly.

For the following assembly steps see chapter 5.

▶ 5 Assembly of the top working platform Tower Models

1102/1104 1106/1116 1108/1110



1. Insert the upper ladder frames (6), (6a) and secure them with spring clips (11). Clip an access deck (10) onto the 5th rung down.

2. Fit the safety protection according to regulations, installing the corresponding four guardrails or two Double guardrails or Uni-Girders .



3. Mount the two toe boards 2.85 m \square between the ladder frames and secure them by adding two end toe boards 0.75 m \square .

Once mounted push guardrails $\boxed{2}$ and Double guardrails $\boxed{9}$ outwards as far as possible.



▶ 6 Adjustment of the mobile beam



The adjustable mobile beam 3 enables you to work close to a wall. When mounted, it may be extended or retracted. Before adjusting it, make sure the ballast weights indicated in the ballast table are placed in the correct positions (page 12). Before adjustment, lower the center jack (M) fixed to the mobile beam 3 as far as possible and secure it.

Release the castors I at the extension arm by winding down the spindle (S) until the extension arm (V), can be moved after loosening the wedge lock (K). Once adjusted, fix the wedge lock (K), and load the castor I by winding up the spindle (S) again. Retract the center jack (M) and secure it.



▶7 Operating the castors



During assembly and while working, the castors 1 must be kept locked by pressing down the brake lever labelled STOP. When the brake is locked, the lever labelled STOP is in the down position. For movement, the castors are unlocked by pushing the other lever down.

▶8 Maximum spindle adjustment of the various models

Assembly with 1323.180 max. 20 cm max. 15 cm max. 30 cm max. 40 cm max. 40 cm max. 60 cm Models: 1124 - 1131 Models: 1102 - 1106 1145 - 1151 Models: 1202 - 1206 Assembly directly on castors Assembly with 1323.320 30 cm 0 cm max. 40 cm

Models: 1101; 1201

Layher Uni Standard Tower

Assembly directly on castors with access ledger







Wall support under load Top view Side view Rolling tower deck 10 14 Top view. with mobile beam Rolling tower deck 10 14 3 Example figure 1204

Layher Uni Standard Tower

For work performed on a load-bearing wall, ballasting can be reduced in accordance with the Ballasting table (see pages 12 and 13). In this case, wall supports must be installed on both sides of the tower. Use the Uni distance tube 18 and fix it to the ladder frame 6, 6a with the couplers 19. The mobile beams must be installed so that they project from the side facing away from the wall.

The wall supports must be attached at the height of the top working platform or at most 1 m below that.

Dismantling



During assembly and dismantling, system decks or scaffolding planks to DIN 4420-3 (minimum dimensions: 28 x 4.5 x 350 cm long) must be installed as auxiliary decks at maximum height intervals of 2.0 m. These auxiliary decks, providing a safe footing for assembly and dismantling, must be removed again after assembly. Each platform must be completely boarded.

Dismantling is in the reverse order to that of the assembly steps.

When dismantling, do not remove the bracing elements such as diagonal braces (B), guardrails 7 or access decks 10 until the ladder frames 6 above them have been dismantled.

To lift out the individual parts, open the snap-on claws by pressing their locking clips. The red locking clips of the decks permit effortless installation and removal by a single person; first open them and place the deck with the opened clips on the rung, then open the opposite clips and lift out the deck.



Towers 1115 and 1116, 1215 and 1216 are intended for outdoor use. The tower base must be assembled as described under 2.3.

Tower model	Ref. No.	1101	1102	1103	1104	1105	1115	1106	1116	1107	1108	1109	1110	1111
Ladder frame 75/4	1297.004	-	2	-	2	-	-	2	2	-	2	-	2	-
Ladder frame 75/8	1297.008	2	2	4	4	6	6	6	6	8	8	10	10	12
Access deck 2.85 m	1242.285	1	1	1	1	2	2	2	2	2	2	3	3	3
Double guardrail 2.85 m	1206.285	2	-	2	-	2	2	-	-	2	_	2	-	2
Guardrail 2.85 m	1205.285	-	5	1	5	7	7	9	9	9	11	13	15	15
Diagonal brace 3.35 m	1208.285	-	2	2	4	4	4	6	6	6	8	8	10	10
Mob. beam, fixed, with deck support	1323.180	-	2	2	2	2	-	2	-	-	-	-	-	-
Mob. beam, adj., with deck support	1323.320	-	-	-	-	-	2	-	2	2	2	2	2	2
Base strut 2.85 m	1324.285	-	1	1	1	1	1	1	1	1	1	1	1	1
Toe board 2.85 m, with claw	1239.285	-	2	2	2	2	2	2	2	2	2	2	2	2
End toe board 0.75 m	1238.075	-	2	2	2	2	2	2	2	2	2	2	2	2
Spring clip	1250.000	-	8	8	12	12	12	16	16	16	20	20	24	24
Castor 200 with spindle, 7 kN	1259.200	4	4	4	4	4	4	4	4	4	4	4	4	4
Ballast	1249.000				For	the numbe	r of ballasti	ng weights	see the bal	asting table	e, page 12			
Tower model	Ref. No.	1201	1202	1203	1204	1205	1215	1206	1216	1207	1208	1209	1210	1211
Ladder frame 75/4	1297.004	-	2	-	2	-	-	2	2	-	2	-	2	-
Ladder frame 75/8	1297.008	2	2	4	4	6	6	6	6	8	8	10	10	12
Access deck 2.85 m	1242.285	-	1	1	1	2	2	2	2	2	2	3	3	3
Deck 2.85 m	1241.285	1	1	1	1	1	1	1	1	1	1	1	1	1
Tower beam 2.85 m	1207.285	2	-	2	-	2	2	-	-	2	-	2	-	2
Guardrail 2.85 m	1205.285	-	4	-	4	6	6	8	8	8	10	12	14	14
Diagonal brace 3.35 m	1208.285	-	2	2	4	4	4	6	6	6	8	8	10	10
Mob. beam, fixed, with deck support	1323.180	-	2	2	2	2	-	2	-	-	-	_	-	_
Mob. beam, adj., with deck support	1323.320	-	-	-	-	-	2	-	2	2	2	2	2	2
Base strut 2.85 m	1324.285	-	-	-	-	-	1	-	1	1	1	1	1	1
Basic tube 2.85 m	1211.285	-	1	1	1	1	1	1	1	1	1	1	1	1
Toe board 2.85 m, with claw	1239.285	2	2	2	2	2	2	2	2	2	2	2	2	2
End toe board 0.75 m	1238.075	2	2	2	2	2	2	2	2	2	2	2	2	2
Spring clip	1250.000	-	8	8	12	12	12	16	16	16	20	20	24	24
Castor 200 with spindle, 7 kN	1259.200	4	4	4	4	4	4	4	4	4	4	4	4	4
Ballast	1249.000				For	the numbe	r of ballasti	ng weights	see the bal	asting table	e, page 12			

For the number of ballasting weights see the ballasting table, page 12

Additional requirement for special structure with 2 bracket deck surfaces										
Aluminium console bracke	t 0.75 m 1341.075	-	4	4	4	4	-	4	-	
Deck 2.85 m	1241.285	-	2	2	2	2	-	2	-	
Ladder frame 75/4	1297.004	-	4	4	4	4	-	4	_	The tower models 1107 – 1111, 1207 – 1211
End toe board	1238.075	-	4	4	4	4	-	4	_	must not be expanded with bracket deck surfaces
Intermediate deck	1339.285	-	2	2	2	2	-	2	_	·····
Spring clip	1250.000	_	8	8	8	8	-	8	_	

When operating with brackets, the tower may be loaded with 1.5 kN/m² (scaffold group 2) at one working level only. A maximum of 2 bracket deck surfaces may be assembled. For rolling tower models 1102 – 1104, 1202 – 1204, the bracket deck surfaces may not be fitted one above the other. When bracket deck surfaces are fitted, the spindles must not be overextended. When bracket deck surfaces are fitted, the corresponding working level must be equipped with complete side protection.



Assembly variants with stabilizers, extendable: 1124 – 1131; with stabilizer, 5 m: 1145 – 1151

Tower model	Ref. No.	1124	1125		1126		1127		1128		1129		1130		1131	
				1145		1146		1147		1148		1149		1150		1151
Ladder frame 75/4	1297.004	2	-	-	2	2	-	-	2	2	-	-	2	2	-	-
Ladder frame 75/8	1297.008	4	6	6	6	6	8	8	8	8	10	10	10	10	12	12
Access deck 2.85 m	1242.285	1	2	2	2	2	2	2	2	2	3	3	3	3	3	3
Double guardrail 2.85 m	1206.285	_	2	2	-	-	2	2	-	-	2	2	-	-	2	2
Guardrail 2.85 m	1205.285	6	8	8	10	10	10	10	12	12	14	14	16	16	16	16
Diagonal brace 3.35 m	1208.285	4	4	4	6	6	6	6	8	8	8	8	10	10	10	10
Stabilizer, extendable	1248.260	4	4	-	4	-	4	-	4	-	4	-	4	-	4	-
Tower support 5 m	1248.500	_	-	4	-	4	-	4	-	4	_	4	-	4	-	4
Rotation preventer	1248.261	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
Toe board 2.85 m, with claw	1239.285	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
End toe board 0.75 m	1238.075	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
Spring clip	1250.000	8	8	8	12	12	12	12	16	16	16	16	20	20	20	20
Castor 200 with spindle, 7 kN	1259.200	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
Access ledger	1344.002	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Ballast	1249.000		For the number of ballasting weights see the ballasting table, page 13													

Ballasting

For ballasting, use Layher ballast weights 20, Ref. No. 1249.000 (10 kg each). A coupler with hand wheel permits simple, quick and secure fixing of the ballast required at the correct places. Only these ballast weights are to be used, liquid or granular ballast materials must not be used. The ballast weights must be distributed evenly to all ballasting fixing points. The remainder not divisible by 4 must be distributed to the fixing points A.

1216 1207 I R Sum I 0 0 0 0 0 0 4 4 0 6 6 0 0 0 0 0 0 0 4 4 0 6 6 0 0 0 0 0 0 0 0 0 1 2	1208 1209 1 R L R L R 0 0 0 0 0 0 8 0 9 9 0 10 0 0 0 0 0 0 0	1210 1211 Sum K K O 0 0 10 0.12 12
R Sum R Sum L 0 0 0 0 0 0 0 4 4 0 6 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 1 1 2 X	R L R L R 0	Sum L R Sum 0 0 0 0 0 10 0 12 12 12
0 0 0 0 0 0 0 4 4 0 6 6 0 0 0 0 0 0 0 0 0 0 0 1 1 2×	0 0 0 0 0 0 0 8 8 0 9 9 0 10 0 0 0 0 0 0 0 0	0 0 0 0
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	8 8 0 9 9 010 0 0 0 0 0 0 0	10 0 12 12
$\begin{array}{c c} 0 & 0 & \bigcirc 0 & 0 & \bigcirc 0 \\ \hline 0 & 0 & \bigcirc 1 & 1 & 2 \\ \end{array}$	0 0 0 0 0 0	
0 0 0 1 1 2 X		
	× ××× ×××	$\times \times \times \times \times$
0 11 11 0 17 17 X	× ××× ×××	$\times \times \times \times \times$
0 0 🔿 1 0 1 X	× ××× ×××	$\times \times \times \times \times$
L R Sum L R Sum L	R Sum L R Sum L R	Sum L R Sum
0 0 0 0 0 0	0 0 0 0 0 0	\circ 0 0 \circ
L R Sum L R Sum L	R Sum L R Sum	
0 0 0 0 0 0	0 0 0 0 0 X X	$\times \times \times \times$
L R Sum L R Sum		
0 2 <mark>2</mark> 0 6 <mark>6</mark> X	$\times \times $	$\times \times \times \times \times$
×× ××× ××	× ××× ×××	$\times \times \times \times \times$
	0 0 1 1 2× 0 1 1 0 1 7× 0 0 1 0 1 1× L R Sum L R Sum L 0 0 0 0 0 0 0 0 L R Sum L R Sum L R Sum L 0	0 0 1 1 2 X

The figures shown indicate the number of ballast weights of 10 kg each.

= no ballast required
 = example on page 17

X = not permissible



Assembly variants with stabilizers, extendable

Tower model			1124		1125		1126		1127		1128		1129		1130		1131
			1224		1225		1226		1227		1228		1229		1230		1231
		I	r Sum	I	r Sum	Т	r Sum	I	r Sum	Ι	r Sum	Ι	r Sum	I	r Sum	I	r Sum
Assembly	in centre position	0	0 🔘	0	0 🔾	0	0 🔾	0	0 🔘	0	0 🔘	0	0 🔘	0	0 🔘	0	0 🔾
indoors		I	R Sum	I	R Sum	Т	R Sum	I	R Sum	Ι	R Sum	Ι	R Sum	I	R Sum	I	R Sum
	in off-centre position	0	7 7	0	99	0	11 11	0	14 <mark>14</mark>	0	16 <mark>16</mark>	0	18 <mark>18</mark>	0	21 21	0	23 <mark>23</mark>
		I	R Sum	I	R Sum	Т	R Sum	I	R Sum	Т	R Sum	Ι	R Sum	I	R Sum	I	R Sum
	off-centre with wall support	0	0 🔘	0	0 🔾	0	0 🔘	0	0 🔘	0	0 🔘	0	0 🔘	0	0 🔘	0	0 🔾
		I	r Sum	Ι	r Sum	Т	r Sum	I	r Sum								
Assembly	in centre position	0	0 🔘	0	0 🔾	0	0 🔘	2	2 4	Х	× ×	Х	××	Х	× ×	Х	××
outdoors		I	R Sum	I	R Sum	Т	R Sum	- 1	R Sum								
	in off-centre position	0	13 <mark>13</mark>	0	19 <mark>19</mark>	0	23 <mark>23</mark>	0	31 <mark>31</mark>	Х	× ×	Х	××	Х	× ×	Х	××
		I	R Sum	Ι	R Sum	Т	R Sum	I	R Sum								
	off-centre with wall support	0	0 🔘	0	0 🔾	0	0 🔘	2	2 4	Х	× ×	Х	X X	Х	××	Х	××

Assembly variants	s with stabilizers, 5 m														
Tower model			1145		1146		1147		1148		1149		1150		1151
			1245		1246		1247		1248		1249		1250		1251
		1	r Sum	Т	r Sum	I	r Sum	Т	r Sum	Ι	r Sum	I	r Sum	I	r Sum
Assembly	in centre position	0	0 🔘	0	0 🔘	0	0 🔘	0	0 🔘	0	0 🔘	0	0 🔘	0	0 0
indoors		1	R Sum	Т	R Sum	I	R Sum	Т	R Sum	I	R Sum	I	R Sum	I	R Sum
	in off-centre position	0	5 <mark>5</mark>	0	7 7	0	9 <mark>9</mark>	0	10 1 <mark>0</mark>	0	12 12	0	13 <mark>13</mark>	0	15 1 <mark>5</mark>
		1	R Sum	Т	R Sum	I	R Sum		R Sum	I	R Sum	I	R Sum	I	R Sum
	off-centre with wall support	0	0 🔾	0	0 🔘	0	0 🔘	0	0 🔘	0	0 🔘	0	0 🔘	0	0 🔘
		1	r Sum	Т	r Sum										
Assembly	in centre position	0	0 🔘	0	0 🔘	×	× ×	Х	××	Х	××	Х	××	Х	× ×
outdoors		1	R Sum	1	R Sum										
	in off-centre position	0	14 14	0	17 17	×	× ×	Х	××	Х	××	Х	××	Х	× ×
		1	R Sum	Ι	R Sum	I	R Sum								
	off-centre with wall support	0	0 🔿	0	0 🔿	0	0 0	Х	××	Х	××	Х	××	Х	XX

The number of weights not divisible by four must be distributed diagonally.

The figures shown indicate the number of ballast weights of 10 kg each.

 \bigcirc = no ballast required

X = not permissible



Attachment of ballast weights







Models:











Attachment of ballast weights

Off-centre position:





Layher Uni Standard Tower L R 3 Hele r Т r -32 Sa. L R

Models: 1102 - 1106

1102 — 1106 1202 — 1206





Models:

1124 — 1131 1145 — 1151

(also applicable for assembly with tower beam similar to 12...)





• Attachment of ballast weights

Centre position with brackets:















Attachment of ballast weights

Double structure:





• Example of assembly, model 1104 Assembly outdoors in off-centre position Ballast: see excerpt from Table, page 12

	1104 1204									
I	٢S	Sum								
0	0	0								
0	4	4								
0	0	0								
4	4	8								
0	9	9								

Stabilizer attachment

Read and understand item 1 "Basic Assembly for Rolling Tower Types Without Mobile Beams" on page 6 before assembly. The fixed and adjustable mobile beams are not included when assembled this way. They are replaced by extendable stabilizers 21.





3	End toe board 0.75 m	1238.075	
4	Deck	1241.285	
	2.03 111		
5	Horizontal diagonal brace adjustable	1318.000	
	Mobile beam sup bolt on	port,	Î
16 17	1.0 m 1.4 m	1325.100 1325.140	
18	Uni distance	1275.110	
	1.1 m		
19	Special tower scr rigid	ew coupler,	
	19 mm WS	1269.019	
	22 mm WS	1269.022	- Alton
20	Ballast (10 kg)	1249.000	at the second se
21	Stabilizer extendable	1248.260	_
22	Stabilizer	1248.500	
	5 111		/
			/
23	Tower rotation lock	1248.261	to to
24	Access ledger	1344.002	
4	Basic tube 2.85 m	1211.285	



Special assembly with brackets

Caution! Risk of accidents if the ballasting table is not complied with.



1. The tower models 1107 - 1111, 1115, 1116and 1207 - 1211, 1215, 1216 may not be extended with bracket deck surfaces.

When brackets are used

- the tower may be loaded with 1.5 kN/m² (scaffold group 2) at one working level only.
- the spindles must not be overextended.

the corresponding working platform must be equipped with complete side protection.

the ladder frames must be assembled in the centre position.

Brackets (25) can be fitted to the tower models 1102 – 1106, 1202 – 1206. The corresponding **ballast** weights (see ballasting table on p. 12) must be attached before fitting the brackets.

2. A maximum of 2 bracket deck surfaces can be fitted to a tower. The bracket deck surfaces can be used either both on one side or one on each side. The bracket deck surfaces can be fitted at any level of the tower where a deck is provided.

For the tower models 1102 - 1106, 1202 - 1204, the bracket deck surfaces may not be fitted one above the other, however 2 bracket deck surfaces can be fitted adjacent to one another.



3. Before fitting the brackets, the side protection with toe boards is dismantled at this point.

4. The tower is assembled in accordance with section 2 (see page 6).

5. At the access 10 level, 2 brackets 0.75 m 25 are bolted on using the couplers in such a way that the rungs of the aluminium brackets 0.75 m 25 are at the same level as the ladder frame rungs 6. The deck 14 is now suspended from the bracket rungs 25. 2 ladder frames 6 are fitted onto the bracket 0.75 m 25 and secured with spring clips 11.

6. The intermediate deck 2.85 m 26 is placed between the deck 14 and the access deck 10 and snapped into the bracket rungs 0.75 m 25.

7. Provision of the regulation side protection depending on the tower model by installation of 2 guardrails [2] or 2 double guardrails[9], or beams 2.85 m [32] (see tower models, page 2).

8. Position the 2 toe boards 2.85 m 🗹 between the ladder frames 🙆 / 🗟 and secure them by inserting end toe boards 🔞.

9. After assembly, push the guardrails $\boxed{2}$, double guardrails $\boxed{9}$ or beam 2.85 m $\boxed{32}$ as far outwards as possible.

10. To attach a second bracket deck surface, the steps $1-9\ \text{are repeated}.$

11. Dismantling of the brackets is in the reverse order to that of the assembly steps. After removal of the brackets, the entire tower can be dismantled as described in "Dismantling" on page 10.

Special assembly with bridging

Tower model	1302	1304	1306
Working height (m)	4.6	6.4	8.4
Scaffolding height (m)	3.64	5.64	7.64
Platform height (m)	2.4	4.4	6.4
Weight (kg)	361.7	413.3	508.1

Ballasting The figures shown indicate the number of ballast weights of 10 kg each.

 \bigcirc = no ballast required X = not permissible

Lavher Uni Standard Tower

Double structure on extended mobile beam (1323.320) with and without tower beam									
Tower model	1302	1304	1306						
	L R Sum	L R Sum	L R Sum						
Assembly indoors	00 🔾	00 🔾	00 🔾						
Assembly outdoors	224	00 🔾	606						

▶1 Basic assembly

1. Observe the general instructions for assembly and use on page 28.

The special assemblies 1302, 1304 and 1306 correspond to the double Uni Standard towers 1102, 1104, 1106, or 1202, 1204 and 1206. No other assembly forms are permitted.



No ballasting is necessary for outdoor assembly either.

The maximum assembly height with a platform height of 6.30 m must be observed without fail.

The castors must not be fully extended.

The tower may be loaded with max. 1.5 kN/m² (scaffold group 2) at one working level only.

2. Insert the castors into the special mobile beam with adjustable spigot 2 and secure them against falling out by tightening the wing screws on the spindle nuts.

3. Connect the mobile beams ☑ by a basic tube ④. The basic tube ④ is fitted onto the projecting spigots at the ends of the mobile beams ☑ and wedged tight after adjustment. Suspend the deck ④ from the support of the mobile beam ☑. Then clamp the base strut ⑤ to the leg of the mobile beam support ☑.

4. Attach 2 adjustable spigots 🖾 as shown in the drawing to the adjustable special mobile beam 🖾 and **tighten** the screws of the adjustable spigot 🖾.

▶2 Assembly of intermediate and top working platforms



5. The further assembly of the ladder frames \bigcirc and of the diagonal braces \bigcirc , guardrail \bigcirc and access decks \boxdot is in accordance with sections 2.3 to 4.0 (see pages 6-8). Ensure that the deck \boxdot is placed centrally beneath the ladder frame \boxdot , with the ladder frame \boxdot placed on the adjusting part of the mobile beam \boxdot determining the position.

6. When assembling the top working platform, omit the guardrails and toe boards on the inside. Now move the access deck III and the deck III apart to insert the bridge deck III between the decks into the ladder frames II. This creates a closed working surface. Move the decks back together after installation so that the maximum gap of 25 mm.

7. Now snap 2 guardrails, 0.58 m 🖾 onto the ladder frames 🙆 , 🗟 . Place 2 toe boards 0.6 m 🖾 on the bridge deck 2.85 m 🖄 and connect them using half-couplers to the ladder frames 🙆 , 🗟 . Complete the side protection with 4 end toe boards 0.75 m 🖾 and 2 toe boards 2.85 m 🖾.

8. Dismantling is in the reverse order. To do so, follow the dismantling sequence (see page 10).

During assembly and dismantling, system decks or scaffolding planks to DIN 4420 (minimum dimensions: 28 x 4.5 x 350 cm long) must be installed as auxiliary decks at maximum height intervals of 2.0 m. These auxiliary decks, providing a safe footing for assembly and dismantling, must be removed again after assembly. Each platform must be completely boarded.

Special assembly with bridging

3 Parts list for special assembly with 2 Uni Standard towers on special mobile beams, adjustable

Tower model	Ref. No.	1302	1304	1306
Ladder frame 75/4	1297.004	4	4	4
Ladder frame 75/8	1297.008	4	8	12
Access deck 2.85 m	1242.285	1	1	2
Deck 2.85 m	1241.285	2	2	2
Tower beam 2.85 m	1207.285	_	_	-
Guardrail 2.85 m	1205.285	8	8	14
Mobile beam 3.2 m, adjustable	1338.320	2	2	2
Spigot, adjustable	1337.000	4	4	4
Diagonal braces 3.35 m, adjustable	1208.285	4	8	12
Base strut 2.85 m	1324.285	1	1	1
Base tube 2.85 m	1211.285	1	1	1
Bridge deck	1343.285	1	1	1
Guardrail 0.58 m	1342.058	2	2	2
Toe board 0.6 m	1340.060	2	2	2
End toe board 0.75 m	1238.075	4	4	4
Toe board 2.85 m, with claw	1239.285	2	2	2
Spring clip	1250.000	16	24	32
Castor 200 with spindle, 7 kN	1259.200	4	4	4

The maximum platform height is 6.3 m, for these applications ballasting is not necessary.

Assembly of special mobile beam, adjustable

Ballasting must in any event be in accordance with the ballasting table, column for off-centre position (see page 12). The ballast weights must be distributed evenly to the fixing points A in the drawing. The assembly instructions must be precisely followed here.

Move the spigots on the mobile beam 2 in such a way that the ladder frames 6 can be fitted in the different positions.

For this purpose, both fixed and adjustable spigots B can be used. **Tighten** the bolts of the adjustable spigot. Level the tower using the adjusting spindles. For further assembly see section 2.3.





	 CERTIFICAT 	CERTIFICATE No. Z1A 08 02 19959 053	
	TIFICADO	Holder of Certificate:	Wilhelm Layher GmbH & Co. KG Ochsenbacher Straße 55 74383 Güglingen-Eibensbach GERMANY
	CER.	Factory(ies):	19959
	ифИКАТ 🔶	Certification Mark:	
	CEPTI	Product:	Scaffold
	•	Model(s):	UniStandard
	調査	Parameters:	see attachment 1
	iliib	Tested according to:	DIN EN 1004:2005 DIN EN 1298:1996
	TIFICATE	The product meets the requirements of the German Equipment and Product Safety Act. The Certification marks shown above can be affixed on the product. The certification marks must not be altered in any way. The use of the GS-Mark is permitted until the listed date, the use of the TÜV-Mark is unlimited, unless it is cancelled. See also notes overleaf.	
	CER	Test report no.:	028-71320787-001
	•	GS-Mark valid until:	2013-03-03
00000	ZERTIFIKAT	Date, 2008-10-13 Page 1 of 7 TÜV SÜD Product Service Gmbł	H - Zqrtifizierstelle - Ridlerstrasse 65 - 80339 München - Germany













General directions for assembly and use

The rolling tower may be used for the scaffolding group as specified in DIN EN 1004.

The user of the rolling tower must comply with the following instructions:

1. The user must check the suitability of the selected rolling tower for the work to be performed (Section 4 of BetrSichV – German Ordinance on Industrial Safety and Health).

2. According to DIN EN 1004:2005-03 the maximum platform height is

- 12.0 m when inside buildings
- 8.0 m when outside buildings

The specifications governing ballasting and components on pages 11 - 13 must be observed. There is a risk of accident if this is not done. Stability and load-bearing capacity are no longer assured. Any variations in assembly that differ from the specifications may require additional design measures. In such a case, the stability and load-bearing capacity would have to be verified for the individual case.

3. The assembly, modification or dismantling of the rolling tower in accordance with the present instructions for assembly and use may only be performed under the supervision of a qualified expert and by technically trained employees after special instruction. Only the scaffolding types shown in these instructions for assembly and use may be used. After assembly and before being put into service, the equipment must be inspected by persons qualified to do so (Sections 4 and 10 of BetrSichV). The inspection must be documented (Section 11 of BetrSichV). During assembly, modification or dismantling, the rolling tower must be provided with a prohibition sign indicating "No access allowed" and be adequately safeguarded by means of barriers preventing access to the danger zone (BetrSichV Annex 2, para. 5.2.5).

4. Before installation, all parts must be inspected to ensure they are in perfect condition. Only undamaged original parts from Layher's mobile working platform systems and spigots must be cleaned of dirt after use. Scaffolding components must be secured against slipping and impacts when transported by truck. Scaffolding components must be handled in such a way that they are not damaged. See the tables on pages 12 – 13 of these instructions for wall bracing and attachment of the ballast weights.

5. In order to assemble the upper sections of the rolling tower, the individual parts must be handed up from one level to the next. Tools and small amounts of materials can be carried up by the personnel, otherwise hoisted up to the working level using transport ropes.

6. The ladder frame joints must always be secured with locking pins.

7. Suitable materials must be inserted underneath to ensure that the scaffolding is perpendicular. The permitted deviation from the perpendicular must not be more than 1 %.

8. Stability must be ensured at every phase of assembly.

9. Toe boards can be omitted from intermediate platforms that are only used for ascent. Small towers in which the deck surface is more than 1.00 m high must include equipment that permits attachment of side protection in accordance with DIN EN 1004:2005-03. **10.** Access up to the working platform is generally only permitted on the inside of the scatfolding. Scatfolding types with an assembly height of less than 1 m are an exception to this rule.

11. Work must not take place on two or more working levels at the same time. The manufacturer must be consulted regarding any variations. If work is to take place on more than one level, they must be fully fitted with 3-piece side protection.

12. It is not permitted to push against adjacent objects (such as walls) when working on mobile working platforms.

13. Lifting gear must not be attached to or used on mobile working platforms.

14. Assembly and movement is only permitted on sufficiently strong surfaces, and only in the longitudinal direction or diagonally. All impacts must be avoided. If the base is widened on one side with wall bracing, movement must always be parallel to the wall. Movement should not be faster than normal walking pace.

15. No personnel and/or loose objects may be on the tower while it is being moved.

16. After movement, the wheels must be locked by pressing down the brake lever.

17. The towers must not be subjected to any aggressive fluids or gases.

18. Mobile working platforms must not be connected by bridging unless a special verification of structural stability is provided. The same applies to all special structures such as suspended scaffolding. The attachment of any bridging elements between one mobile working platform and a building is also not permitted.

19. When used in the open air, or in open buildings, the mobile working platform must be moved to an area protected from the wind or secured by other suitable means to prevent it falling over if the wind strength exceeds 6 on the Beaufort scale, or at the end of the working shift. (Wind that exceeds strength 6 can be recognized from the difficulty felt when walking into the wind.) If possible, rolling towers used outside buildings should be securely fastened to the building or to some other structure. It is recommended that mobile working platforms are anchored down if they are left unsupervised. The scaffolding must be aligned perpendicular either by use of the compensating screw, or by inserting suitable materials underneath. The permitted deviation from the perpendicular must not be more than 1%.

20. Decks can also be raised or lowered one rung in order to obtain a different working height. In that case it is necessary to make sure that the specified side protection heights of 1.0 m and 0.5 m are maintained. When assembled this way, deck diagonals are to be used.

The manufacturer must be consulted regarding a stability verification.

 $\ensuremath{\textbf{21}}$. The access hatches must always be kept closed except when climbing through them.

- 22. All couplers are to be tightened up to 50 Nm.
- 23. It is forbidden to climb over from rolling towers.
- 24. Jumping onto the deck surfaces is forbidden.

25. A check must be made on whether all the parts, auxiliary tools and safety equipment (ropes etc.) needed for assembly of the mobile working platforms are available on the building site.

26. Horizontal and vertical loads that could cause the mobile working platform to tip over must be avoided. These include:

- forces caused by pushing against adjacent objects (e.g. walls)
- additional wind loads (the tunnel effect of buildings with through-passages, buildings without facings or building corners).

27. Mobile beams, stabilizers or outriggers and ballast must be installed if specified.

28. It is forbidden to increase the height of the deck surfaces by using ladders, boxes or any other objects.

29. Mobile working platforms are not designed to be lifted or suspended.

30. The item numbers for components given in blue in the text refer to the list of individual parts on page 19.

All dimensions and weights are guideline values. Subject to technical modification.

Our deliveries shall be made exclusively in accordance with our currently valid General Terms of Sale.



More Possibilities. The Scaffolding System.

Wilhelm Layher GmbH & Co. KG Scaffolding Grandstands Ladders Post Box 40 74361 Gueglingen-Eibensbach Germany Phone +49 7135 70-0 Fax +49 7135 70-372 E-Mail export@layher.com www.layher.com